

CTX 607_Vx V.92 PCI Modem

FEATURES:

- PCI Version 2.2 compliant
- Up to 56kbps V.92 data rate*
- Support operating systems such as Windows 98/2000/ME/XP and Linux
- PCI Softmodem

SPECIFICATIONS

Modem Standard

Modem Standard

- V.92 (down-stream) up to 56,000 bps*;
(Including fast connect, modem on hold, pcm upstream)
- V.34bis (up to 33,600 bps)
- V.34 (2,400 to 28,800 bps)
- V.32bis, V.32, V.22bis, V.22/Bell 212A, V.21/Bell 103

Fax Standard

- Group 3, class 1
- EIA Class fax commands
- V.17 (14,4K bps), V.29 (9,6K bps), V.27ter (4.8K bps),
V.21 (300bps), ITU-T T.31 Class 1 FAX

Approvals:

- EN55022, EN55024, EN60950, TS103021

Supply voltage:

- 3.3V +/- 0.3V

Power dissipation:

- ~230mW

Line Interface:

- Europe

PCB Revision:

- CTX607

Chipset:

- Agere SV92PL
- Agere CSP 1034C

*Due to power limitation in the telephone network data receiving is possible up to 54,3 kbps maximum only.

ORDERCODE

- CTX607_Vx V.92 Modem